

## MirroFlex® Structures and Flat Sheets **Technical Information and Product Specs**

Need installation instructions? Scan here to visit our website!





## **Description**

- MirroFlex® Structures are decorated thermoplastic sheets with high impact resistance and are available in a wide variety of patterns and colors. They can be used as a value-added product in areas that vertical grade High-Pressure Laminates (HPL) are typically used.
- Unlike HPL, MirroFlex® Structures can easily be cut to size with razor knives or scissors. It can also be applied to many substrates with pressure-sensitive adhesive strips and be used for retrofits and DIY applications.
- Sizes These are textured dimensional products, so actual pattern thickness varies, but raw material is 0.030" thick.
  - o 4' x 8' Wall Panels
  - o 4' x 10' Wall Panels
  - o 2' x 2' Ceiling Tiles
  - o 2' x 4' Ceiling Tiles
- Most product ships with clear protective film or with Tuffcote™
- **UPS Shippable**

## **Applications**

Commercial Market Uses:

Office - desks, storage cabinets, reception, etc.

Education – cabinets, high impact areas

Healthcare – furniture, equipment, high impact areas

Hospitality – restaurants, bar & counter fronts, hotels/motels

Store & Bank Fixtures

Interior Doors, Kiosk Fronts & Elevator Cab Interiors-including high impact areas

Wall Panels & Signage

Recreational Market Uses:

**Boat Interiors** 

Coach Interiors

Residential Market Uses:

Occasional Furniture – tables, cabinets, etc. Novelty and Juvenile Furniture

DIY and Renovations

Technical Information	Test	Results
Fire Retardant	ASTM E-84	Class A
QUV		Minimum of 100 hours
Solvent Resistance		50 MEK
Humidity		12 hrs 96-100% RH @ 40 degrees C on MDF
MEK Double Rubs/Crockmeter		Withstands 70 cycles



Technical Information	Test	Results
Impact Resistance	ASTM D5420	> 2-inch lbs per mill of thickness
Abrasion Resistance Patina with TuffCote		4,700*
Argent Finishes	TABER	5,000*
EccoFlex Paintable		1,000*

**Fire Rating Information:** Most MirroFlex Structures sheets and ceiling tiles are fire rated and are designed to pass ASTM E 84 Class A.

## **Stain Resistance Properties**

Stain Resistance Testing		Group 1		Group 2		Group 3		Group 4		Group 5		Group 6	
#	Materials	24	7	24	7 Day	24	7	24	7 Day	24	7 Day	24	7
		Hrs	Day	Hrs		Hrs	Day	Hrs		Hrs	_	Hrs	Day
1	Wesson Oil	Ν	Ζ	Ν	Ζ	Ν	Ν	Ν	Ν	Ν	S	Ν	Ζ
2	Household Ammonia	Ν	Ζ	Ν	Ζ	Ν	Ν	Ν	Ν	S	S	Ν	Ζ
3	409 all purpose cleaner	Z	N	S	S	N	Ν	Ν	N	Ν	N	Ν	Z
4	"Tide" laundry detergent	N	N	Ν	Ν	N	N	N	N	N	N	N	N
5	Isopropyl Alcohol	Ν	Ν	S	S	Ν	Ν	Ν	Ν	Ν	Ν	Ν	Ν
6	Clorox	Ν	Ν	S	Ν	L	L	L	L	L	L	Ν	Ν
7	Grape Juice	Ν	Ν	N	Ν	Ν	Ν	Ν	N	Ν	Ν	Ν	Ν
8	Orange Juice Concentrate	N	N	Ν	Ν	N	N	N	N	N	N	N	N
9	Coffee	Ν	Ν	Ν	Ν	Ν	Ν	Ν	N	Ν	S	Ν	Ν
10	Mustard	Ν	Ν	Z	Ν	Ν	Ν	Ν	Ν	S	S	Ν	Ν
11	Ketchup	Ν	Ν	Ν	Ν	Ν	Ν	Ν	Ν	Ν	Ν	Ν	Ν
12	Red wine	Ν	Ν	Ν	Ν	Ν	Ν	Ν	Ν	Ν	Ν	Ν	Ν
13	Coca-Cola	Ν	Ν	Ν	Ν	Ν	Ν	Ν	Ν	Ν	Ν	N	Ν
14	Water	Ν	Ν	Ν	Ν	Ν	Ν	Ν	Ν	Ν	Ν	N	Ν
15	Black crayon	Ν	И	Ν	Z	Ν	Ν	Ν	Ν	Ν	Z	L	L
16	Lipstick	Ν	Ν	Ν	Ν	Ν	Ν	Ν	Ν	Ν	Ν	L	L
17	Pine-Sol	Ν	И	S	S	Ν	Ν	Ν	Ν	Ν	Z	Ν	Z
18	Vinegar	Ν	Ν	Ν	Ν	Ν	Ν	L	L	Ν	Ν	Ν	Ν
19	Steel Wool	Ν	Ν	Ν	Ν	Ν	Ν	Ν	Ν	Ν	Ν	Ν	Ν
20	Tea	Ν	И	Ν	Z	Ν	Ν	Ν	Ν	Ν	Z	Ν	Z
21	Windex® Surface Cleaner	Ν	N	Ν	N	N	N	N	N	Ν	N	N	N
22	Scotch-Brite® w/Soap	Ν	Ν	Z	Ν	Ν	Ν	Ν	N	Ν	Ν	Ν	Ν

Group 1 - Patina, Brushed Aluminum, Paintable, Mirror Red, Argents

Group 2 - Woodgrains

Group 3 - Mirror Silver

Group 4 - Mirror Gold

Group 5 - Brushed Copper

Group 6 - EccoFlex Paintable

N = no change

S = slight change

M = medium change

L = large change

\*No Sign of Wear